

# Gaco Western

S I N C E 1 9 5 5

## Product Data Sheet:

**GacoFlex 66B**

**October 2011**

Supersedes 12/06

### **GACOFLEX® 66B POLYESTER REINFORCING TAPE**

**DESCRIPTION:** GacoFlex 66B parchment-like texture tape is made of fusion bonded fabric polyester fibers laid in random orientation. It exhibits a high tensile strength, good elongation and a low profile.

**USAGE:** Plywood joints, concrete construction joints, concrete cracks, and joints between metal, fiberglass or insulation, and combinations of the above substrates in roof, deck and wall specifications. The 66B tape can also be used for flashing at changes of plane; however, installation into inside corners requires special care.

**COLOR:** White

#### **APPLIED PRODUCT DATA**

**TENSILE:** ASTM D-412-68 400 psi (2.76 MPa) Transverse  
800 psi (5.52 MPa) Longitudinal

**ELONGATION:** ASTM D-412-68 60%

**ADHESION:** ASTM D-903-49 Same as that of Primer used.

**SOLVENT SWELL:** None measurable.

**HEAT SHRINKAGE:** None after 6 months at 150°F (66°C).

#### **PACKAGED PRODUCT DATA**

**LENGTH:** 100 Yards per roll (91.44 m)

**THICKNESS:** 5 Mils (.13mm)

**STORAGE:** Store in a cool, dry place.

#### **APPLICATION**

Refer to General Instructions GW-1-2 and Details GW-5-D2.

